

## GEWICHTSTABELLEN STANDAARD-CONSTRUCTIELIGGERS

H (mm)	7,0 / 4,5 / 5,0**			8,0 / 5,0 / 5,0 **			8,0 / 6,0 / 6,0			10,0 / 4,5 / 5,0**			10,0 / 5,0 / 5,0**			10,0 / 6,0 / 6,0			12,0 / 6,0 / 6,0		
	kg/m	lg (m)	st/pak	kg/m	lg (m)	st/pak	kg/m	lg (m)	st/pak	kg/m	lg (m)	st/pak	kg/m	lg (m)	st/pak	kg/m	lg (m)	st/pak	kg/m	lg (m)	st/pak
50	0,923			1,104			1,353			x	x	x	x	x	x	x	x	x	x	x	x
60	0,936	14	50	1,121			1,376			1,249			1,342			1,597	14	50	x	x	x
70	0,950	14	50	1,139	14	50-100	1,402	14	100	1,264	14	50	1,361	14	100	1,623	14	50	x	x	x
80	0,966	14	50	1,161	14	100	1,431			1,280	14	50	1,382			1,652	14	50	x	x	x
90	0,983	14	50	1,183	14	50-100	1,461	14	100	1,297			1,405			1,683	14	50			
100	1,002	14	100	1,207	14	100	1,494	14	100	1,315	14	50	1,429	14	100	1,715	14	50			
110	1,021	14	100	1,232	14	100	1,528	14	100	1,334			1,454	14	100	1,750	14	50			
120	1,040	14	50	1,258	14	100	1,564	14	100	1,354	14	50	1,480			1,786	14	50			
130	1,060	14	100	1,285	14	50-100	1,601	14	100	1,374			1,506			1,822	14	50			
140	1,081	14	50	1,313	14	50-100	1,638	14	100	1,395	14	50	1,534			1,860	14	50			
150	1,103	14	50-100	1,341	14	50-100	1,677	14	100	1,416			1,562	14	100	1,898	14	50			
160	1,124	14	50-100	1,369	14	100	1,716	14	100	1,438	14	50	1,591			1,937	14	50			
170	1,147	14	50-100	1,398	14	50-100	1,755	14	100	1,460			1,620	14	100	1,977	14	50			
180	1,169	14	50	1,428	14	50	1,796	14	50	1,482			1,649	14	50	2,017	14	50			
190	1,192	14	50	1,457	14	50	1,836	14	50	1,505			1,679	14	50	2,058	14	50			
200	1,214	14	50	1,487	14	50	1,877	14	50	1,528			1,709	14	50	2,098	14	50			
210	1,237	14	50	1,518	14	50	1,918	14	50	1,551			1,739			2,140	14	50			
220	1,260	14	50	1,548	14	50	1,960			1,574			1,770	14	50	2,181	14	50			
230	1,284			1,578	14	50	2,002			1,597			1,800			2,223	14	50			
240	1,307			1,609	14	50	2,043			1,621			1,831	14	50	2,265	14	50			
250	x	x	x	1,640	14	50	2,086			1,644			1,862	14	50	2,307	14	50			
260	x	x	x	1,671	14	50	2,128			1,668			1,893	14	50	2,350	14	50			
270	x	x	x	1,703	14	50	2,170			1,692			1,924			2,392	14	50			
280	x	x	x	1,734	14	50	2,213			1,716			1,956			2,435	14	50			
290	x	x	x	1,765	14	50	2,256			1,740			1,987			2,478					
300	x	x	x	1,797	14	50	2,299			1,764			2,019			2,521	14	50			
310	x	x	x	1,828			2,342			x	x	x	x	x	x	2,563	14	25			
320	x	x	x	1,860			2,385			x	x	x	x	x	x	2,606	14	25			
330	x	x	x	1,892			2,428			x	x	x	x	x	x	2,650	14	25			
340	x	x	x	1,923			2,471			x	x	x	x	x	x	2,693	14	25			
350	x	x	x	1,955			2,514			x	x	x	x	x	x	2,736					
360	x	x	x	1,987			2,558			x	x	x	x	x	x	2,779	14	25			
370	x	x	x	2,019			2,601			x	x	x	x	x	x	2,823					
380	x	x	x	2,051			2,645			x	x	x	x	x	x	2,866					
390	x	x	x	2,083			2,688			x	x	x	x	x	x	2,910					
400	x	x	x	2,115			2,732			x	x	x	x	x	x	2,953					

\*\* volgens DIN 1045-1 van 21-04-2011 (ISB gewichtsberekening)

voorraadproduct

geen voorraadproduct, te verkrijgen op bestelling. Minimale lengte 1,80m, maximale lengte 14,00m steeds in veelvoud van 10cm.

x - geen mogelijkheden