

## Warmgewalst betonstaal B500B

HWL.GR-B500B



	Stuks / pak			KG/M
	6 m 1500 kg / pak	12 m 2500 kg / pak	14 m 2500 kg / pak	
ø 8	+/- 630	+/- 530	+/- 450	0,395
ø 10	+/- 400	+/- 340	+/- 290	0,617
ø 12	+/- 280	+/- 235	+/- 200	0,888
ø 14	+/- 207	+/- 172	+/- 147	1,208
ø 16	+/- 160	+/- 132	+/- 115	1,578
ø 20	+/- 100	+/- 83	+/- 72	2,466
ø 25	+/- 65	+/- 54	+/- 46	3,853
ø 32		+/- 32	+/- 28	6,313
ø 40		+/- 21	+/- 18	9,865

## Afmetingen



## Technische Klasse B500B - BE500TS

Mechanische karakteristieken	Rekgrens Re (Mpa)	Verhouding Rm / Re	Totale rek bij maximale kracht Agt %
Minimum karakteristieke waarde Cv	500	1,08	5,5

Certificaten Intersig nv



Certificaten Intersig France sarl



Certificaten Van Merksteijn Steel bv



Voor de up-to-date scope van onze certificaten verwijzen wij u graag door naar onze website.